

# AC/DC converter

Micro SMPS

www.easypower.in

## AC/ DC converter

## Features

- **Universal Input : 110- 260 VAC**
  - **Operating Temperature Range : 0°C - +50°C**
  - **High isolation voltage up to 1kV**
  - **Regulated output, low ripple and noise**
  - **High efficiency, high reliability**



SO12V2000 Micro SMPS – a compact size power converter offered by *EASY POWER*. It features universal input voltage, taking AC/DC voltage, low power consumption, high reliability, and safer isolation.

Input Specification					
Item	Operating condition	Min.	Typ.	Max.	Unit
Input Voltage Range	AC input	110		260	VAC
Input Voltage Range	DC input	150		300	VDC
Input frequency		50		50	Hz
Leakage current		0.1 mA RMS typ. 230 VAC/50 Hz			
Recommended external input fuse		1A/ 250V, slow fusing, necessary.			

Output Specification					
Item	Operating conditions	Min.	Typ.	Max	Unit
Output voltage accuracy	12V output	-	±0.2	-	%
Line regulation	Full load	-	±0.5	-	
Load regulation	0% - 100% load	-	±1	-	
Ripple & Noise	20 MHz bandwidth (Pk – Pk) value	-	200	400	mV
Output current		-	1800	2000	mA
Temperature drift coefficient		-	±0.02	-	%/°C
Min Load		0	-	0	%
Isolation voltage – Input voltage	Test time: 1min	1000	-	-	VAC
Operating Temperature		0	-	+50	°C
Storage Temperature		0	-	+60	°C
Storage Humidity		-	-	90	%RH
Welding Temperature	Wave soldering	260 ± 5°C; time 5 – 10s			
	Manual welding	360 ± 10 °C; time 3 – 5s			
Switching frequency		-	100	-	kHz


# AC/DC converter



## Micro SMPS

Physical Specification	
Casing Material	Black colour, heat resistant
Packaging Dimension	80.00 x 55.00 x 25.00
Weight	40 gm (Typ.)
Cooling method	Free air convection

## Footprint -



All dimensions are in **millimetre**.

Product height is of 25 mm

Product width is of 55 mm

Product length is of 80 mm